

Fresh Mix Dispenser with 3 Hoppers

ITEM#

PROJECT

DATE



Model FMD-3

Dimensions: 30"H x 11.3"W x 23.3"D
(76.2 cm H x 28.7 cm W x 59.2 cm D)



FMDS-3
front display panel

Features

Fresh Mix Dispenser

- Variable speed motors allow control of product consistency in mixing chamber (.75 to 6.6 grams of powder per second).
- Lighted front graphics for merchandising are easy to exchange: cappuccino or soup.
- Attractive high-impact resin door is dent and scratch resistant. Black finish or stainless with black door.
- Large easy-to-fill translucent hoppers hold 4 lbs. (1.81 kg) of product each, ensuring quick and timely refilling.
- High speed heavy-duty whipper for complete product mixing.
- Improved automatic rinsing of whipper reduces run-on after beverage is dispensed.
- Adjustable legs and drip tray accommodate 20 oz. (.59 litre) mugs easily.
- Electrical and plumbing components easily accessible through front and top.
- International electrical configurations available.

FMD DBC Dispenser

- Easy-to-program, one-touch portion control for 3 cup sizes.
- Fast fill perfect for quick service restaurants.
- Each mixing chamber has independent powder to water ratio.
- System setup is password protected for safety.
- Simple setup and hopper throw calibration system.



Model FMD DBC-3

Dimensions: 30"H x 11.3"W x 23.3"D
(76.2 cm H x 28.7 cm W x 59.2 cm D)



Model FMD-3 available
with optional Cafe Display

For current specification sheets and other information, go to www.bunn.com.

Model	Agency Listing
FMD-3	NSF, UL
FMDS-3	NSF, UL
FMD DBC-3	NSF, UL

Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity	Cu. Ft.	Shipping Weight	Cord Attached
FMD-3 BLK	SET00.0197	120	15	1700	1800	5.2 gal./hr.**	8.1 ft ³	86 lbs.	Yes*
FMD-3 BLK ^f	SET00.0332	120	15	1700	1800	5.2 gal./hr.**	8.1 ft ³	86 lbs.	Yes*
FMD-3 SS	SET00.0198	120	15	1700	1800	5.2 gal./hr.**	8.1 ft ³	86 lbs.	Yes*
FMDS-3 BLK [†]	28600.0000	120	15	1700	1800	5.2 gal./hr.**	8.1 ft ³	84 lbs.	Yes*
FMD DBC-3 BLK	29250.0000	120	15	1700	1800	5.2 gal./hr.**	8.1 ft ³	85 lbs.	Yes*

[†]Model has soup dispense tips and graphic. *Power cord (NEMA 5-15P) 15 Amp-120V machine only. **Based on incoming water temperature of 60°F. ^fCafe display.

Door Conversion Kit—From model HC (black decor only) to model FMD door - 28613.0000

Note: SS=stainless steel cabinet with black door, BLK=black decor.

Electrical: 120V model requires 2-wires plus ground service rated 120V, single phase, 60 hz. 120/240V model requires 3-wires plus ground service rated 120/208 or 120/240V, single phase, 60Hz.

Plumbing: 20-90 psi (138-621 kPa) from a 3/8" or larger supply line. A shut-off valve should be installed in the line before the unit. Install a regulator in line when pressure is greater than 90 psi to reduce it to 50 psi. Supplied with 1/4" male flare fitting.

